

ACME LEAD SCREWS



Centerless ground and standard rolled
2G threadform

PHONE: 516.328.3300 • FAX: 516.326.8827 • WWW.SDP-SI.COM



> MATERIAL:

300 Series Stainless Steel


> SPECIFICATIONS:

Lead accuracy of ± 0.010 " per foot.

Straightness of 0.010" per foot.



**INCH COMPONENT
CATALOG NUMBER**



Screw Size Code	Screw Size	No. of Starts	Root Dia. in.	Lead in.	Available Lengths ft.
*25201	1/4-20	1	.19	.050	1, 3
*25161	1/4-16		.17	.063	
31082	5/16-8	2	.23	.250	1, 3, 6
31084		4		.500	
31122	5/16-12	2	.167		
*37081	3/8-8	stub	.29	.125	
37084		4	.27	.500	
Δ 37055	3/8-5	5	.24	1.000	
Δ 37045	3/8-4			1.200	
*37101	3/8-10	1	.26	.100	
37102		2		.200	
37114	3/8-11	4	.27	.375	
*37121	3/8-12	1	.28	.083	
37122		2	.31	.167	
*37161	3/8-16	1	.30	.063	
43082	7/16-8	2	.36	.250	2, 4, 6
43084		4		.500	
*50101	1/2-10	1	.39	.100	
50102		2		.200	
*62081	5/8-8	stub	.125		
*62101	5/8-10	1	.52	.100	
62102		2		.200	
*75061	3/4-6	1	.56	.167	
*75081	3/4-8		.61	.125	
*75101	3/4-10		.63	.100	
10005	1-5		.78	.200	
10008	1-8		.86	.125	
10010	1-10		.88	.100	

*Left-hand threads available on special order.
Δ Fast lead high helix lead screws.

