



Catalog Number	Standard Length (L_0)	G/g	Max. Length	Rail Width ± 0.05	M_1 Height	F Spacing	$d_1 \times d_2 \times h$	Rail Weight kg/m
BBRAILMHSR15	160, 220, 280, 340, 460, 640 & 820	20	1600	15	15	60	4.5 X 7.5 X 5.3	1.5
BBRAILMHSR20	220, 280, 340, 460, 640, 820, 1000 & 1240	20	2200	20	18	60	6 X 9.5 X 8.5	2.3
BBRAILMHSR25	220, 280, 340, 460, 640, 820, 1000, 1240, 1600 & 3000	20	2500	23	22	60	7 X 11 X 9	3.3
BBRAILMHSR30	280, 440, 600, 760, 1000, 1240, 1640, 2040, 2520 & 3000	20	3000	28	26	80	9 X 14 X 12	4.8
BBRAILMHSR35	280, 440, 600, 760, 1000, 1240, 1640, 2040, 2520 & 3000	20	3000	34	29	80	9 X 14 X 12	6.6
BBRAILMHSR45	570, 885, 1200, 1620, 2040, 2460 & 2985	22.5	3000	45	38	105	14 X 20 X 17	11
BBRAILMHSR55	780, 1020, 1260, 1500, 1980, 2580 & 2940	30	3000	53	44	120	16 X 23 X 20	15.1
BBRAILMHSR65	1270, 1570, 2020 & 2620	35	—	63	53	150	18 X 26 X 22	22.5

NOTES: 1. To complete the catalog number, add the standard length (L_0) to the end.
(i.e., for 160mm length **BBRAILMHSR15160**)
2. See page 121 for matching blocks.